

## BB-100 Infant Incubator

### ©Function features :

- Temperature displayed by LED
- Alarm functions : Power failure; Over temperature; Temperature deviation; Temperature sensor failure; Fan failure
- >37°C temperature setting
- A keypad lock prevent inadvertent changes the setting
- A second thermal cut-out function for more safety
- Humidity is adjustable continuously
- Heating power displayed on panel
- The infant bed inclination angle is adjustable
- Raw Material is Aluminium Magnesium Alloy agaiant rust

# BB-100 INFANT INCUBATOR

Standard NO.: YZB/N0244-2002  
 Registration NO.: 2005 NO.3540922  
 License NO. Of manufacture : HNFDA NO. 20070031

## Product main characteristic

### Product main characteristic:

- ※ Trough for pulling and pushing ,which is convenient to add the water and wash
- ※ Fan with low noise and long life-span
- ※ Temperature deviation and over temperature could be amended in front panel directly
- ※ Silence/reset button for alarms
- ※ Six operating windows,two side access operating windows can be swiveled
- ※ Support bracket, convenient and practical

### Standard configuration:

Main body(including the transparent hood, control system, infant bed, water trough);

I.V.pole; Mattress; Support bracket; Castors;  
 Rs232 connector;

### Optional parts:


- Phototherapy up side unit;
- Phototherapy from up and down sides;
- Infant bed pulled from side door;

## Technical data

Technical data		
Power supply		AC110/220V 60/50Hz
Power input		420VA
Operating conditions	Environment temperature	20℃~30℃
	Environment relative humidity	30%~75%RH
	Environment air velocity of flow	<0.3m/s
Air Temperature control range		25℃~38℃
Temperature fluctuation		±0.5℃
Uniformity of mattress temperature		≤0.8℃
Warm-up time		≤45min
Internal noise level		≤55dB(A)
Infant bed tilt angle		±10°
Mattress size		65cm(L)*37cm(W)
Trough capacity		1200ml
Air filter		0.5um



Phototherapy up sideBL-30LED



Phototherapy down sideBL-100LED



Side door hood

## Transport and storage

### Transport and storage:

Environment Temp: -10℃--+70℃  
 Environment Relative Humidity: ≤80%  
 Atmospheric Pressure: 500 ~ 1060hPa

### Package:

Each unit is packed in one wooden crate  
 ※ Size :110\*78\*86CM  
 ※ N.W.:72KG G.W.:102KG

ZHENGZHOU DISON INSTRUMENT AND METER CO.,LTD

Add: 10F, Torch Building B, Zhengzhou High and New Technology Development Zone, Henan, CHINA  
 TEL: +86-371-67897160 FAX: +86-371-67897162  
 Http://www.zzdison.com E-mail: info@zzdison.com

ISO9001 ISO13485 CE